

Grun Model SB7 Strawblower – COMPETITIVE COMPARISON

	Grun SB7	Finn B70
Power	<ul style="list-style-type: none"> Diesel Kubota V 1505, 33.5 hp (25kw), 4 cylinder water cooled diesel engine with over-center clutch. 	<ul style="list-style-type: none"> Diesel Kubota V 1505, 33.5 hp (25kw), 4 cylinder water cooled diesel engine with over-center clutch.
Engine Safety System	<ul style="list-style-type: none"> Low oil pressure, high water temperature shutoff. 	<ul style="list-style-type: none"> Low oil pressure, high water temperature shutoff.
Fuel Tank Capacity	<ul style="list-style-type: none"> 17 gal. (64 liters). 	<ul style="list-style-type: none"> 13.5 gal. (51 liters).
Capacity	<ul style="list-style-type: none"> Up to 7 tons of hay or straw per hour. 	<ul style="list-style-type: none"> Up to 7 tons of hay or straw per hour.
Range	<ul style="list-style-type: none"> 65 feet (21.3m) in still air. 	<ul style="list-style-type: none"> 60 feet (18m) in still air.
Feed	<ul style="list-style-type: none"> Manual. 	<ul style="list-style-type: none"> Manual.
Beater Chamber	<ul style="list-style-type: none"> 7.5 cubic foot (0.21 cubic meters) with removable adjustable beater chains. 	<ul style="list-style-type: none"> 3.5 cubic foot (0.10 cubic meters) with removable beater chains.
Discharge Spout	<ul style="list-style-type: none"> Ball bearing surface. 360 degree horizontal rotation and 70 degree vertical travel. 	<ul style="list-style-type: none"> Block bearing mounted. 360 degree horizontal rotation and 70 degree vertical travel.
Blower	<ul style="list-style-type: none"> Dynamically balanced, 21" (53 cm) diameter, 6 blade fan with a discharge velocity greater than 170 mph (274 km/h) - discharge velocity equals the wind speed of a Class 5 Hurricane. 	<ul style="list-style-type: none"> Dynamically balanced, 21" (53 cm) diameter fan with 6 blades developing a discharge velocity greater than 150 mph (240 km/h).
Feed Tray	<ul style="list-style-type: none"> Folding tray, turnbuckle adjustable to meet bed height of supply vehicle. 	<ul style="list-style-type: none"> Folding tray, adjustable height to meet bed of supply vehicle.
Drive	<ul style="list-style-type: none"> Blower fan in-line attached to over-center clutch with flexible coupling. Fan shaft extends all the way through the beater chamber and is securely frame mounted at both ends - reduces vibrations, helps eliminate splitting weld seams. 	<ul style="list-style-type: none"> Blower fan in-line coupled to over-center clutch with flexible coupling and two pillow block bearings.
Weight	<ul style="list-style-type: none"> SB7T – 2,450 lbs. (1,111 kg). SB7S – 1,800 lbs. (816 kg). 	<ul style="list-style-type: none"> B70T – 2250 lbs. (1,020 kg). B70S – 1,590 lbs. (721 kg).
Trailer Option	<ul style="list-style-type: none"> Independent suspension rubber torsion axle, ST205/75R/15 load range B, highway tread radial tires or equal, fenders, D.O.T. highway lights, dual skid proof operator platforms, parking jack, 2" (5 cm) ball or heavy duty eye hitch. 	<ul style="list-style-type: none"> Independent suspension rubber torsion axle, 75R/15 load range B, highway tread radial tires, fenders, D.O.T. highway lights, dual skid proof operator platforms, parking jack, 2" (5 cm) ball or heavy duty eye hitch.
Brakes	<ul style="list-style-type: none"> Electric with breakaway switch standard. Hydraulic surge brakes optional. 	<ul style="list-style-type: none"> Electric with breakaway switch.